

### Section I - Identity

<b>Product Name</b> P-1500 Portion-Stik, 2 part Epoxy Putty		
<b>Manufacturer's Name</b> Glenmarc Manufacturing Inc.	<b>Emergency Telephone Number (800)</b> 255-3924 CHEM-TEL	
<b>Manufacturer's Address</b> 25661 Hillview Court Mundelein, Illinois 60060		<b>Date Prepared</b> APRIL 2010
<b>Importer's Name &amp; Address</b> Alldec Trading Ltd.. #108 – 19329 Enterprise Way, Surrey, BC, V3S 6J8	<b>Information Numbers</b> Tel: (604) 534-3688 Fax: (604) 534-0166	

### Section II - Hazard Ingredients/Identity Information

<b>Hazardous Components</b>			
Product Class: Epoxy Putty		Hazard Ratings: Health: 1	
C.A.S. Number: N/A		none-extreme Fire: 1	
		0 - 4	Reactivity: 0
<b>Ingredients</b>	<b>Weight</b>	<b>Exposure Limits-----</b>	<b>VP</b>
<b>Ingredients CAS#</b>	<b>%</b>	<b>OSHA/PEL</b>	<b>mm Hg</b>
<b>ACGIH/TLV</b>			
Glycidyl ethers of 25068-38-6	13.05 NE	NE NE	0
Bisphenol A resins	STEL= NE	NE NE	0
Tri(dimethylaminomethyl) 90-72-2 phenol	1.37 NE	NE	
( *NE= Not established )			
<b>Other Ingredients</b>	<b>CAS#</b>	<b>%</b>	
Crystalline Silica	14808-60-7	31	
Magnesium silicate hydrate	14807-96-1	41	
Sodium calcium magnesium silicate	65997-17-3		
1.5			
Polyether polymercaptan	Trade Secret	12	
Zinc Sulfide	N/A	1	

### Section III - Physical/Chemical Characteristics

<b>Boiling Range</b> N/A	<b>Vapor Density</b> Non-volatile
<b>Liquid Density</b> Heavier than water	<b>Volatiles Volume</b> %o Wgt. %0
<b>Weight Per Gallon</b> 16.20 pounds	<b>Evaporation Rate</b> 0.0 X n-Butyl Acetate
<b>Appearance</b> Putty	

## Section IV - Fire and Explosive Hazard Data

Flash Point None F TOC		LEL None	UEL None
Extinguishing Media Water spray, foam, CO <sub>2</sub> , dry chemicals			
Special Fire Fighting Procedures None			
Unusual Fire and Explosion Hazards CO, Aldehydes, acids, oxides of sulfur & nitrogen may be formed.			

Page 1 of 2

## Section V - Reactivity Data

Stability Stable	Conditions to Avoid None
Incompatibility (Materials to Avoid) None	
Hazardous Decomposition or Byproducts CO, aldehydes, acids, oxides of sulfur and nitrogen.	
Hazardous Polymerization Will not occur	Conditions to Avoid None

## Section VI - Health Hazard Data

Permissible Exposure Limits N/A
Effects of Overexposure Inhalation: None Ingestion: Irritation of intestinal tract Skin Contact: Possible irritant and sensitizer Eye Contact: Possible irritant and sensitizer
Emergency and First Aid Procedures <b>Ingestion:</b> Induce vomiting. <b>Eye Contact:</b> Flush with water, consult a physician. <b>Inhalation:</b> N/A <b>Skin Contact:</b> Wash with soap and water.

## Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled Spills or Leaks: dispose of in a normal manner; <b>NOT A HAZARDOUS MATERIAL!</b>
Waste Disposal Method Incinerate in furnace or bury in landfill according to applicable regulations.
Precautions to be Taken in Handling and Storage Avoid eye contact and excessive skin contact.
Other Precautions Wash with soap and water immediately after use. If sanding cured putty or substrates, wear eye protection and dust mask.

## Section VIII - Control Measures

<b>Respiratory Protection</b>	None required
<b>Protective Gloves</b>	Polyethylene gloves for prolonged use
<b>Eye Protection</b>	Safety glasses
<b>Other Protective Clothing or Equipment</b>	None required
<b>Ventilation: General Mechanical:</b> None required	<b>Local Exhaust:</b> only if heated above 100° F (38° C)