

Material Safety Data Sheet U.S. Department of Labor Occupational Safety and Health
Administration Form Approved OMB No. 1218-0072

Section I - Identity

Product Name P-1500W Wood Epoxy Putty, 2 part Epoxy Putty		
Manufacturer's Name Glenmarc Manufacturing Inc.	Emergency Telephone Number (800) 255-3924 CHEM-TEL	
Manufacturer's Address 25661 Hillview Court Mundelein, Illinois 60060		Date Prepared April 2010
Importer's Name & Address Alldec Trading Ltd. 108-19329 Enterprise Way, Surrey, BC V3S 0L5	Information Numbers Tel: (604) 534-3688 Fax: (604) 534-0166	

Section II - Hazard Ingredients/Identity Information

Hazardous Components		
Product Class: Epoxy Putty Hazard Ratings: Health: 1 C.A.S. Number: N/A none-extreme Fire: 1 0 - 4 Reactivity: 0		
Ingredients Weight	Exposure Limits-----	VP
Ingredients CAS# %	OSHA/PEL	mm Hg
ACGIH/TLV	NE NE	0
Glycidyl ethers of 25068-38-6 21.85 NE	NE NE	
Bisphenol A resins STEL= NE	NE NE	0
Tri(dimethylaminomethyl) 90-72-2 1.52 NE		
phenol		
Other Ingredients CAS#	(*NE= Not established)	
Magnesium silicate hydrate 14807-96-1		
Sodium calcium magnesium silicate 65997-17-3		
	Trade	
Polyether polymercaptan	Secret	

Section III - Physical/Chemical Characteristics

Boiling Range N/A	Vapor Density Non-volatile
Liquid Density Heavier than water	Volatiles Volume %O Wgt. %O
Weight Per Gallon 7.90 pounds	Evaporation Rate 0.0 X n-Butyl Acetate
Appearance Putty	

Section IV - Fire and Explosive Hazard Data

Flash Point None F TOC		LEL None	UEL None
Extinguishing Media Water spray, foam, CO ₂ , dry chemicals			
Special Fire Fighting Procedures None			
Unusual Fire and Explosion Hazards CO, Aldehydes, acids, oxides of sulfur & nitrogen may be formed.			

Page 1 of 2

Section V - Reactivity Data

Stability Stable	Conditions to Avoid None
Incompatibility (Materials to Avoid) None	
Hazardous Decomposition or Byproducts CO, aldehydes, acids, oxides of sulfur and nitrogen.	
Hazardous Polymerization Will not occur	Conditions to Avoid None

Section VI - Health Hazard Data

Permissible Exposure Limits N/A
Effects of Overexposure Inhalation: None Ingestion: Irritation of intestinal tract Skin Contact: Possible irritant and sensitizer Eye Contact: Possible irritant and sensitizer
Emergency and First Aid Procedures Ingestion: Induce vomiting. Eye Contact: Flush with water, consult a physician. Inhalation: N/A Skin Contact: Wash with soap and water.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled Spills or Leaks: dispose of in a normal manner; NOT A HAZARDOUS MATERIAL!
Waste Disposal Method Incinerate in furnace or bury in landfill according to applicable regulations.
Precautions to be Taken in Handling and Storage Avoid eye contact and excessive skin contact.
Other Precautions Wash with soap and water immediately after use. If sanding cured putty or substrates, wear eye protection and dust mask.

Section VIII - Control Measures

Respiratory Protection	None required
Protective Gloves	Polyethylene gloves for prolonged use
Eye Protection	Safety glasses
Other Protective Clothing or Equipment	None required
Ventilation: General Mechanical: None required	Local Exhaust: only if heated above 100° F (38° C)